# CEE 260/MIE 273: Probability and Statistics in Civil Engineering M1c: Case studies and experiments

Prof. Oke

**UMassAmherst** 

College of Engineering

September 9, 2025

#### Outline

• Recap: Quantiles and boxplots

Colab Examples

# Your expectations (Fall 2025)




#### Quantiles

Quantiles are cutoff points that partition an ordered sample or dataset into equal-sized groups.

- A median splits a sample into two: m
- Two terciles split a sample into 3 groups: T<sub>1</sub>, T<sub>2</sub>
- Three **quartiles** split a sample into 4 groups:  $Q_1, Q_2, Q_3$
- Four **quintiles** split a sample into 5 groups:  $QU_1$ ,  $QU_2$ ,  $QU_3$ ,  $QU_4$
- ...
- Ninety-nine **[per]centiles** split a sample into 100 groups:  $P_1, \ldots, P_{99}$

## Quantiles (cont.)

Certain quantiles are equivalent to others:



- The median is the second quartile  $Q_2$
- ullet The 25th percentile is equivalent to the first quartile  $Q_1$

Sextiles  $(S_1, S_2, ...)$  partition a distribution into 6 equal groups.

- How many sextiles are there?
- **2** The second sextile  $S_2$  can be expressed as which tercile?<sup>a</sup>

Answers: Q1: There are 5 sextiles; Q2:  $S_2 = T_1$  (first tercile)


<sup>a</sup>Recall that a tercile splits a sample into 3 equal groups.

Colab Examples

## Using boxplots

A boxplot<sup>1</sup> displays the distribution of data

- Useful for identifying outliers
- Efficient for comparing multiple datasets
- The lines indicating the "maximum/minimum" points (excluding outliers) are called whiskers



 $<sup>\</sup>mathbf{1}_{\mathsf{Figure}} \ \mathsf{source} \colon \mathtt{https://towardsdatascience.com/understanding-boxplots-5e2df7bcbd51}$ 

### Google Colaboratory

We will begin our introduction to Python via basic statistical analyses using the Google Colab platform (https://colab.google/).

```
For an introduction, visit: https:
//www.mathworks.com/help/matlab/getting-started-with-matlab.html.
```

#### Notebooks

Today, we will use the following Notebooks:

- m1-blind-stork.ipynb https://colab.research.google.com/drive/ 1G2\_UPPli1rdfWv\_9wRJvT-m2kLwg3GFu?usp=sharing
- m1-usa-housing.ipynb https://colab.research.google.com/drive/ 1onpllyTzNuo09op89WDR4ft7o\_U-eJVL?usp=sharing

#### Bonus Example

#### Example 1: Walking cadence

In the article "Can We Really Walk Straight?" (Amer. J. of Physical Anthropology, 1992: 19–27) reported on an experiment in which each of 20 healthy men was asked to walk as straight as possible to a target 60m away at normal speed.

Consider the following observations on cadence (number of strides per second): .95 .85 .92 .95 .93 .86 1.00 .92 .85 .81 .78 .93 .93 1.05 .93 1.06 .96 .81 .96

Summarize the data; interpret and discuss.


### To be assigned: Iris dataset

We will explore the properties and applications of boxplots using the following datasets:

- Popularized in Ronald A. Fisher's classic 1936 paper, "The Use of Multiple Measurements in Taxonomic Problems" https://onlinelibrary.wiley. com/doi/10.1111/j.1469-1809.1936.tb02137.x
- Data collected by Edgar Anderson on various measurements of 3 species of Iris flowers
- Also found on the UCI Machine Learning Repository. Data available by default on MATLAB

#### Example 2: Iris species

#### Three species of the *Iris* flower:



Iris Setosa

Iris Virginica

Figure: Iris species (Source:

https://s3.amazonaws.com/assets.datacamp.com/blog\_assets/Machine+Learning+R/iris-machinelearning.png)

### Recap

- Pre-survey review
- Python/Colab Introduction:
  - Summarizing data
  - Visualizing data: histograms, boxplots

#### Problem Sets

- PS1 due at 1pm today
- PS2 will be assigned this afternoon